


Stellringe

leichte Ausführung - mit Gewindestift
adjusting rings, light range

DIN 705

Form A



d 1 H 8	b js 14	d 2 h 13	d 3	d 4 h 11	Gew.-Stift				Stahl	V2A
5	6	10	M 3	1,5	M 3 x 4				LG	LG
6	8	12	M 4	1,5	M 4 x 5				LG	LG
7	8	12	M 4	1,5	M 4 x 5				LG	LG
8	8	16	M 4	2	M 4 x 6				LG	LG
10	10	20	M 5	3	M 5 x 8				LG	LG
12	12	22	M 6	4	M 6 x 8				LG	LG
15	12	25	M 6	4	M 6 x 8				LG	LG
16	12	28	M 6	4	M 6 x 8				LG	LG
18	14	32	M 6	5	M 6 x 8				LG	LG
20	14	32	M 6	5	M 6 x 8				LG	LG
22	14	36	M 6	5	M 6 x 10				LG	LG
24	16	40	M 8	6	M 8 x 12				LG	LG
25	16	40	M 8	6	M 8 x 10				LG	LG
26	16	40	M 8	6	M 8 x 10				LG	LG
28	16	45	M 8	6	M 8 x 12				LG	LG
30	16	45	M 8	6	M 8 x 10				LG	LG
32	16	50	M 8	8	M 8 x 12				LG	LG
34	16	50	M 8	8	M 8 x 12				LG	LG
35	16	56	M 8	8	M 8 x 12				LG	LG
36	16	56	M 8	8	M 8 x 12				LG	LG
38	16	56	M 8	8	M 8 x 12				LG	LG
40	18	63	M 10	8	M 10 x 16				LG	LG
42	18	63	M 10	8	M 10 x 16				LG	LG
45	18	70	M 10	8	M 10 x 16				LG	LG
50	18	80	M 10	10	M 10 x 16				LG	LG
55	20	80	M 10	10	M 10 x 16				LG	LG
60	20	90	M 10	10	M 10 x 16				LG	LG
65	20	100	M 10	10	M 10 x 20				LG	LG
70	20	100	M 10	10	M 10 x 20				LG	LG
75	22	110	M 12	10	M 12 x 20				LG	LG
80	22	110	M 12	10	M 12 x 20				LG	LG
90	22	125	M 12	12	M 12 x 20				LG	LG
100	25	140	M 12	12	M 12 x 25				LG	LG

LG - Lagerartikel - Preise auf Anfrage

Werkstoff: Stahl entsprechend Normvorschrift

Werkstoff: V2A - 1.4301 oder 1.4305

andere Werkstoffe und Abmessungen aus Vorrat oder kurzfristig lieferbar, bitte anfragen