


## Sechskantmuttern

hexagon thin nuts

# DIN 936



d	Steigung Regelgew.	m	s	e			14 H	17 H	22 H	WW Gewinde	WW 14 H
M 8	1,25	5	13	14,38			LG	LG			
M 10	1,5	6	17	18,9			LG	LG	LG		
M 12	1,75	7	19	21,1			LG	LG	LG	1/2 "	LG
M 14	2	8	22	24,49			LG	LG	LG		
M 16	2	8	24	26,75			LG	LG	LG	5/8 "	LG
M 18	2,5	9	27	29,56			LG	LG	LG		
M 20	2,5	9	30	32,95			LG	LG	LG	3/4 "	LG
M 22	2,5	10	32	35,03			LG	LG	LG	7/8 "	LG
M 24	3	10	36	39,55			LG	LG	LG	1 "	LG
M 27	3	12	41	45,2			LG	LG	LG	1 1/8 "	LG
M 30	3,5	12	46	50,85			LG	LG	LG	1 1/4 "	LG
M 33	3,5	14	50	55,37			LG	LG	LG	1 3/8 "	LG
M 36	4	14	55	60,79			LG	LG	LG	1 1/2 "	LG
M 39	4	16	60	66,44			LG	LG	LG	1 3/4 "	LG
M 42	4,5	16	65	71,3			LG	LG	LG		
M 45	4,5	18	70	76,95			LG	LG	LG		
M 48	5	18	75	82,6			LG	LG	LG	2 "	LG
M 52	5	20	80	88,25			LG	LG			
M 56	5,5	22	85	93,56			LG	LG	LG		
M 60	5,5	25	90	99,21			LG				
M 64	6	28	95	104,86			LG				

**LG** - Lagerartikel - Preise auf Anfrage

**Werkstoff:** Stahl entsprechend Normvorschrift

andere Werkstoffe, Abmessungen und Festigkeitsklassen aus Vorrat oder kurzfristig lieferbar, bitte anfragen